ACMI #24

STAMP PAD INK

POROUS

SUBSTRATES

Description:
ACMI #24 was formulated for marking paper, corrugated, wood and other porous substrates from a stamp pad, flexographic printer, or other printing method using rubber type. Pad life is excellent and dry time is fast.

SPECIFICATIONS:	Meets: A-A-209a Ink, Stamp Pad
Applications:	Foam or felt stamp pad, flexographic printer, or other method using rubber type, inline carton coder
Viscosity:	35 cps
Specific Gravity:	1.15
Weight per Gallon:	9.58 lbs.
Flashpoint:	>240° F.
Dry time:	2-4 seconds Variations in temperature and humidity may affect dry time.
Shelf Life & Storage:	Use within 1 year is recommended. Ink should be stored at normal room temperature and capped tightly after each use.
Chemical Base:	Water
Colorant Base:	Dye
RECONDITIONER:	#6 Reconditioner
COLORS:	Black, Violet, Blue, Green, Red

AVAILABILITY:	Pints, Quarts and Gallons Smaller sizes available on request

QUALITY ACMI INKS

STATEMENT OF LIABILITY

Neither the manufacturer nor the seller shall be liable for any injury, loss or damage arising out of the use of this product. The only obligations of the manufacturer or the seller shall be to replace any quantity of this product found to be defective or, at the option of the seller or manufacturer, to refund the purchase price. The purchaser or user of this product should, before use of the product, determine whether it is suitable for that use. The user assumes all risk and liability in connection with that use.

THE FOREGOING IS IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED