# ACMI #4134
# STENCIL
# NONPOROUS

Description:
ACMI #4134 was formulated for stenciling on nonporous substrates. This ink can be applied by roller with pad or brush or by fountain brush or roller. #4134 is resistant to petroleum solvents.
Meets: A-A-208B Type I
Formerly: TT-I-1795

**SPECIFICATIONS:**

| | |
|---|---|
| Applications: | Stencil roller with pad or brush and fountain brush or roller |
| Viscosity: | 160 cps |
| Specific Gravity: | 1.09 |
| Weight per Gallon: | 9.09 lbs. |
| Flashpoint: | 110° F. |
| Dry time: | 2 - 4 minutes<br>Variations in temperature and humidity may affect dry time. |
| Shelf Life & Storage: | Use within 1 year is recommended. Ink should be stored at normal room temperature and capped tightly after each use. |
| Chemical Base: | Solvent |
| Colorant Base: | Pigment |
| **RECONDITIONER:** | #4134 Reconditioner |
| **COLORS:** | Black, White, Blue, Gray, Bronze, Yellow, Orange, Green, Red, Brown |
| **AVAILABILITY:** | Pints, Quarts and Gallons<br>Smaller sizes available on request |

QUALITY ACMI INKS

STATEMENT OF LIABILITY

Neither the manufacturer nor the seller shall be liable for any injury, loss or damage arising out of the use of this product. The only obligations of the manufacturer or the seller shall be to replace any quantity of this product found to be defective or, at the option of the seller or manufacturer, to refund the purchase price. The purchaser or user of this product should, before use of the product, determine whether it is suitable for that use. The user assumes all risk and liability in connection with that use.

THE FOREGOING IS IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED